

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
10 February 2005 (10.02.2005)

PCT

(10) International Publication Number
WO 2005/012988 A1

(51) International Patent Classification: **G02F 1/1335**

(21) International Application Number:
PCT/KR2004/001933

(22) International Filing Date: 30 July 2004 (30.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10-2003-0053131 31 July 2003 (31.07.2003) KR
10-2004-0008419 9 February 2004 (09.02.2004) KR

(71) Applicant (for all designated States except US): **DOOSAN CORPORATION ELECTRO-MATERIALS BG** [KR/KR]; 602 Yongje-dong, Iksan-city, Jeollabuk-do 570-350 (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HWANG, Jang-Hwan** [KR/KR]; 433-4 Gasuwon-dong, Seo-ku, Daejeon 302-800 (KR). **PAE, Chong-Pil** [KR/KR]; 108-1402, Neulpureun-Byeonsan Apartment, Mangpo-dong, Paldal-ku, Suwon-city, Kyeonggi-do 442-400 (KR). **KOOK, Min-Cheol** [KR/KR];

103-904, Bowon Apartment, 692, Pungdeokcheon-dong Pungdeokcheon-ri, Suji-eub, Yongin-City, Kyeonggi-do 449-846 (KR).

(74) Agent: **DARAE PATENT FIRM**; 10th Floor, KIPS, 647-9, Yeoksam-dong, Kangnam-ku, Seoul 135-980 (KR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: **PRISM SHEET HAVING CONCAVE PENTAGONAL**



(57) Abstract: A prism sheet having a concave pentagonal structure is disclosed. The prism sheet comprises a base layer, and a prism array disposed on and supported by the base layer. The prism array is composed of a plurality of prisms aligned in parallel and one beside the other. The transversal cross-section of each prism has a shape of concave pentagon, which is symmetrical about a vertical line passing the apex. The interior angle α of the apex is $30^\circ \leq \alpha \leq 120^\circ$, the exterior angle β formed by the upper slant side and the lower slant side is $\beta < 180^\circ$, the interior angle γ of the lower vertex formed by the lower slant side and the base is $5^\circ \leq \gamma \leq 85^\circ$ and the length w of the base is $30\mu\text{m} \leq w \leq 100\mu\text{m}$. Preferably, the interior angle α of the apex may be $40^\circ \leq \alpha \leq 100^\circ$, the exterior angle β formed by the upper slant side and the lower slant side may be $160^\circ \leq \beta \leq 179^\circ$, and the interior angle γ of the lower vertex formed by the lower slant side and the base may be $30^\circ \leq \gamma \leq 60^\circ$. Preferably, the length w of the base may be $40\mu\text{m} \leq w \leq 60\mu\text{m}$.